LARGE FORMAT PRINTER SURECOLOR™ SC-P5000



COLOUR PRECISION. PHOTOGRAPHIC BRILLIANCE.

Epson presents you the benchmark in photographic quality - the SC-P5000 with superior colour reproduction. With Epson's PrecisionCore[™] printhead, it produces images with incredible details and consistency. In addition, the UltraChrome[™] HDX all-pigment ink set delivers outstanding colour accuracy and image durability in ultra-high resolution, with a wide colour gamut that achieves the most dynamic images.





ENGINEERED FOR BUSINESS

Advanced Printhead Technology

Highly advanced PrecisionCore printhead technology delivers incredibly consistent and accurate ink droplet placement.



Shooth grac

Photographic and Proofing Accuracy The Epson UltraChrome HDX ink technology delivers accurate colours with superb black density, achieving smooth gradations and optical clarity. **Efficient Workflow Solutions**

Epson's innovative software solutions enhance printing processes, achieving affordable professional output.

SPECIFICATIONS SURECOLOR™ SC-P5000



Model Number		SC-P5000		Dir
Printing Technology	Printing Method	PrecisionCore printhead		SC
		Epson Variable-Sized Droplet Technology		
	Black Nozzle Configuration	Light Light Black ink is used: 360 nozzles each color (x3) Violet ink is used: 360 nozzles each color (x2)		We
	Color Nozzle Configuration	Light Light Black ink is used: 360 nozzles each color (x7)		
		Violet ink is used: 360 nozzles each color (x8)		
	Print Direction	Bi-directional printing, uni-directional printing		
		Auto Head Alignment technology Auto Nozzle Check technology		
		Auto Switching between Photo BK and Matte BK		*
Delat Quellite	Maximum Davah dian	Bar-code Print System		
Print Quality	Maximum Resolution Minimum Ink Droplet Volume	2880 x 1440 dpi		
Performance*1	Draft Mode	3.5pl 0.5 minutes		500
	Normal Mode			6
	Fine Mode	720 x 720dpi, 1.8 minutes		E
	Super Fine Mode	720 x 720dpi, 1.8 minutes		
Ink System		Epson UltraChrome HDX		*1 F
		Cyan, Photo Black, Matte Black, Vivid Magenta, Yellow, Orange, Green, Light Cyan,		san
		Vivid Light Magenta, Light Black, Light Light Black*2		mo tim
		Cyan, Photo Black, Matte Black, Vivid Magenta	a, Ye ll ow, Orange, Green, Light Cyan,	soft
		Vivid Light Magenta, Light Black, Violet*2		net
Ink Capacity		200ml/80ml (Bundled)		*2 l
Printer Software on CD-ROM	Printer Driver	WindowsXP/Vista/7/8/8.1/10 (32/64bit) or later/MacOSX10.6.8 or later Windows Server 2003 Standard/Standard *64bit,		eith
on CD-ROM		2008 Standard/Standard *64bit/R2,		ma late
		2012 or later (Certification/Logo: Windows Server 2008/2002	8B2)	with
Paper Handling	Paper Path	(Certification/Logo: Windows Server 2008/2008R2)		989
aper manuling	Roll Dimensions	Friction Feed (Auto switching between cut sheet and roll paper)		Ink 20
		203mm-432mm, 2incn-core/3incn-core 2inch-core: Maxφ103mm/3inch-core: Maxφ150mm		201 • F
	Paper Size (width)	203mm (8") - 432mm (17"): Roll paper		• (
	Thickness 203mm (8") - 432mm (17"): Cut Sheet			• \
		0.08-0.50mm: Ro ll paper 0.08-1.50mm: Cut Sheet		• \
	Borderless			• [
		10/14/16/17inch, A4/A3/A3+, 300mm: Cut paper		• \
	ASF Capacity: Max. sheets	ASF Cassette: Plain paper 250 sheets (A4-A2/US-C)		• L
Control Panel	Color & Size	2.7 inch Color LCD		• N
	Number of Dots	960 x 240 pix.		• L
nterface		Hi-Speed USB, 10BASE-T/100BASE-TX/1000BASE-T		• C
Control Code		ESC/P raster		• (
Memory	Printer Main	256MB (Main)/128MB (Network)		• \
Environmental Characteristics	Temperature	Operating: 10°C - 35°C Storage: -20°C - 40°C		Su
	Humidity	Operating: 20 - 80% (no condensation)		Sp
	•	Storage: 5 - 85% (no condensation)		- 1-
Electrical Characteristics	Voltage	AC 100-240V 50-60Hz		
	Rated Current	0.70.4A		
	Power Consumption	Operating: Approx. 52 W		
		Ready: Approx. 20W Sleep: Approx. 5W *Interface is 1000BASE-T		Rc
				Pri
	0 10 1 10(4)	Power off (Stand-by): Less than 0.5W		Inł
coustic Noise Level	Sound Pressure Level <db(a)></db(a)>	Less than 47dB(A)		Bo
	Sound Power Level <b(a)></b(a)>	Less than 6.2B(A)		Ma
Utility Software for Windows OS	PC Software for Windows OS	Printer Driver Installer Package	Epson Color Calibration Utility Manual Launcher	Cle
		User's Guide (EN) Network Guide (EN)	Software Updater	
		LFP RemotePanel 2	Adobe ICC Profile EpsonNet Setup	
			EpsonNet Config	-
			EpsonNet Print	E Contraction of the second seco
oftware from Web	PC Software for Windows OS	LFP Accounting Tool (Job monitoring, consumable cost tracking)	EpsonNet Setup Manager CopyFactory	0
download for Windows OS	WINDOWS US	(Job monitoring, consumable cost tracking) Epson Print Layout		F
		Firmware Updater (Firmware Package)		v s
Jtility Software for	PC Software for	Installer Package		V
Macintosh OS	Macintosh OS	Epson Color Calibration Utility		C
Software from Web Jownload for	PC Software for Macintosh OS	Printer Driver User's Guide (EN) Network Guide (EN)	EpsonNet Setup Epson Print Layout	p
Macintosh OS		Manual Launcher	Firmware Updater (Firmware Package)	n
		Software Updater	Uninstaller (Only MacintoshOS)	o tł
System	System Requirement	Windows XP/Vista/7/8/8.1/10	Macintosh Mac OS X10.6.8 or later	S
		(32/64bit) or later CPU: Core 2 Duo 3.05GHz	CPU: Core 2 Duo 3.05GHz Memory: Memory more than 1GB	c
		Memory: Memory more than 1GB	HDD: Free space more than 32GB	c
		HDD: Free space more than 32GB	TIDD. THEE Space THORE Main 520D	f

EPSON INDIA PVT. LTD.

12th Floor, The Millenia, Tower A, No.1, Murphy Road, Ulsoor, Bangalore - 560 008. Tel: 080-30515000 Fax: 080-30515005

Regional Offices:

Ahmedabad - 3314 8500/01, Chennai - 3967 7500, Cochin - 4012 315, Coimbatore - 98942 19200, Kolkata - 6500 9370/77, Mumbai - 3079 8200, New Delhi - 3312 0300/01, Pune - 3028 6000/05, Hyderabad - 6463 9640/41

Call: SOUTH Alok Singh 098405 03210, Harishankar 098802 85075 NORTH Akhtar Imam 099101 08780, Ashutosh Kumar 098153 94550, Sudhir Kumar 093898 35156 EAST Sourov Kumar 098746 72616 WEST Milind 098209 74733, Devendra 098509 49453. Email: vasu@eid.eps on.co.in



Epson Helpline: For product info or service - 1800 425 0011 EPSON For service - 1860 3000 1600 (9AM - 6PM) (Mon - Sat) Email: ehtp@eid.epson.co.in

www.epson.co.in





766mm 363mm



A2: 420 x 594mm

ures represent print times only for the Epson test e image as shown, produced on Plain (draft-fine s). Print speeds are engine only with total throughout lependent on workflow configuration, paper type, are, file format/size, print resolution, ink coverage, rking, and other factors.

ers need to choose to configure the machine with light light black or violet. Once this choice has been , it is final and cannot be undone or switched at a ime. 99% Pantone coverage requires configuration iolet ink. Configured with light light black provides Pantone coverage.

artridge Compatibility

200ml Ink Cartridges				
Photo Black	C13T913100			
• Cyan	C13T913200			
 Vivid Magenta 	C13T913300			
• Yellow	C13T913400			
 Light Cyan 	C13T913500			
 Vivid Light Magenta 	C13T913600			
 Light Black 	C13T913700			
 Matte Black 	C13T913800			
 Light Light Black 	C13T913900			
Orange	C13T913A00			
• Green	C13T913B00			
• Violet	C13T913D00			
Supplies & Optional Accessories				

Spectroproofer	SpectroProofer
	Mounter 17"
	(C12C890631)
	+ LS30EP
	(C12C932021)
Roll Media Spindle	C12C811251
Printer Cutter Blade	C12C815351
Ink Maintenance Box	C13T619000
BorderFree	C13T619100
Maintenance Box	
Cleaning Sheet	C13S400045



017 Epson India Pvt. Ltd. All Rights erved. Reproduction in part or in whole, out the written permission from Epson, is etty prohibited. EPSON and EXCEED YOUR ON are registered trademarks of Seiko Epson poration. All other product names and other pany names used herein are for identification poses only and are the trademarks or stered trademarks of their respective ers. Epson disclaims any and all rights in e marks. Print samples shown herein are ulations. The actual product design and tents may vary. Specifications are subject to nge without notice and may vary between ntries. Please check with local Epson offices nore information.

Information correct at time of printing Printed January 2018

Dealer's Stamp